

## DTCM230-258-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications		
Magnification (x)	0.044	
Object Field of View (Фmm)	258	
Working Distance (mm)	340±5	
Max Sensor Size (Фmm)	11.4(2/3")	
Best Aperture (F/#)	4.9	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>180	
Depth of Field (mm)	±225@F11	
Length of I/O (mm)	788±5	



Field of View (mm × mm)		
1/1.8" EV76C570 (7.2x	(5.4)	163.6x122.7
1/1.7" IMX226 (7.5x5	.6)	170.5x127.3
2/3" IMX250/264 (8.45)	(7.1)	192.0x161.4
Mechanical Specifications		
Mount		С
Length (mm)		429.9
Compatible Lighting		
Telecentric LED Lighting		LP270-90

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



