

DTCM111-48-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications		
Magnification (x)	0.383	
Object Field of View (Фmm)	48	
Working Distance (mm)	128±3	
Max Sensor Size (Фmm)	18.4(1.1")	
Best Aperture (F/#)	7.2	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>115	
Depth of Field (mm)	±4.3@F16	
Length of I/O (mm)	312±3	

Field of View (mm × mm)		
1" IMX183 (13.13x8.76)		34.3x22.9
1.1" IMX253 (14.19x10.38)		37.0x27.1
Mechanical Specifications		
Mount		С
Length (mm)		166.7
Weight (kg)		0.6
Compatible Lighting		
Telecentric LED Lighting	DTCL-48-xW-y	
	Beam Diameter 48mm	
Weight (kg) 0.6 Compatible Lighting Telecentric LED Lighting DTCL-48-xW-y		

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

