

## DTCM110-300-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications		
Magnification (x)	0.055	
Object Field of View (Фmm)	300	
Working Distance (mm)	465±6	
Max Sensor Size (Фmm)	16.6(1")	
Best Aperture (F/#)	6.5	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>135	
Depth of Field (mm)	±211.6@F16	
Length of I/O (mm)	1134±6	



Field of View (mm × mm)		
1" PYTHON 5000(12.43x9.83)		226.0x178.7
1" IMX255(14.19x7.51)		258.0x136.5
1" IMX183(13.13x8.76)		238.7x159.3
Mechanical Specifications		
Mount		С
Length (mm)		651.5
Weight (kg)		46.7
Compatible Lighting		
Telecentric LED Lighting	DTCL-300-xW-y	
	Beam Diameter 300mm	

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

